

Declaration of performance

DoP JPH-030

- Unique identity code of the product type: DUO / TRIO laminated timber spruce without preservative treatment
 Intended use: Building structures and bridges
- 3. Manufacturer: Johann Pabst Holzindustrie Holzinnovationszentrum 1 8740 Zeltweg Austria
- 4. Authorised representative: No external authorised representative
- 5. System for assessment and examination of consistency of performance:

System 1

6.	Harmonised standard:	EN 14080:2013
	Notified body:	Nr. 1359-CPR-0633

7. Declared performances:

Performance				
Mechanical properties as				
Mechanical properties of strength classes C 24 to EN 338				
Widths from 100 mm bis 280 mm Heights from 100 mm bis 280 mm Lengths up to 18 m The respective product dimensions can be retrieved from the accompanying documents.				
Adhesive strength as				
30 N/mm²				
Delamination test according to EN 14080, Appendix C, Method B				
Durability of adhesive strength as				
Norway spruce (Picea Abies), silver fir (Abies Alba) Adhesive for finger joints: PUR, adhesive type I Adhesive for surface gluing: MUF, I90 GP 0,3 S				
Durability against biological infestation as				
5				
see "Geometrical data" Characteristic raw density of the respective strength class				



Type of wood	Norway spruce (Picea Abies), silver fir (Abies Alba)			
Fire behaviour as				
Fire behaviour class	D-s2, d0 according to EN 14080, table 11			
Emission of formaldehyde as				
Formaldehyde emission class	E 1			
Release of further hazardous substances				
Release of further hazardous substances	not relevant			

The performance of the above product corresponds to the declared performances. The above-stated manufacturer is solely responsible for the preparation of the performance declaration in accordance with the Regulation (EU) No. 305/2011.

Untersigned for the manufacturer and on behalf of the manufacturer by:

Reinhard Pabst Managing Director

Zeltweg, 11.11.2021

Fc. hund Volk

.....

(Place and date of issue)

(signature)