

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

Glued laminated timber (glulam) Block glued glulam

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

JOHANN PABST HOLZINDUSTRIE GMBH

Holzinnovationszentrum 1

AT-8740 Zeltweg

and produced in the manufacturing plant

AT-8740 Zeltweg, Holzinnovationszentrum 1

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14080:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0633

Date of first issue: 24.07.2015

Date of issuance: 21.03.2023

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforchung.at.



Dr. Andreas Neumüller
Authorised signatory



Dr. Manfred Brandstätter
Head of the Certification Body

Addendum to certificate 1359-CPR-0633

Date of issuance: 21.03.2023

Scope of certification for the following products:

GLUED LAMINATED TIMBER (GLULAM)

Timber species/ strength classes:	PCAB - spruce; ABAL - fir: GL 20h, GL 24h, GL 28h, GL 30h GL 24c, GL 28c, GL 30c
Mechanical resistance:	according to EN 14080
Service classes:	1, 2, 3
Adhesive:	
- Finger joints	manufacturing plant 1 Type I: MUF according to EN 301 manufacturing plant 2 Type I: PUR according to EN 15425
- Surface bonding	manufacturing plant 1 Type I: MUF according to EN 301 manufacturing plant 2 Type I: MUF according to EN 301
Reaction to fire:	D-s2, d0
Formaldehyde class:	E1
Natural durability class:	according to EN 350-2

BLOCK GLUED GLULAM

Timber species:	PCAB - spruce; ABAL - fir
Cross-sectional shape:	rectangular
Adhesive – block joint:	Type I: MUF according to EN 301